

Quick pipe



Quick-Pipe combines the advantages of cable duct and installation pipe in an intelligent system. This system allows tidy and safe surface-mounted installation of all kinds of cables on walls and ceilings. Quick pipe is available in four metric sizes: M16, M20, M25 and M32. The stock length is 2 m.


The system is VDE-tested and achieves a protection rating of IP44. The Quick-Pipe can be used in the temperature range between -25 and +60°C and is resistant against impact energy of 5 J.

The fittings are a component part of the system. The smallest shipped quantity is one shipping box.

Type	Size	Colour	Length mm	Dimen- sion t mm	Dimen- sion C mm	Pack. m	Weight kg/100 m	Item No.
2953 M16 LGR	M16	Light grey	2000	1,2	8,2	50	7,000	2153904
2953 M20 LGR	M20	Light grey	2000	1,5	10	40	11,500	2153912
2953 M25 LGR	M25	Light grey	2000	1,6	13,6	30	16,000	2153920
2953 M32 LGR	M32	Light grey	2000	1,7	—	20	21,500	2153939
2953 M16 RW	M16	Pure white	2000	1,2	8,2	50	7,700	2153960
2953 M20 RW	M20	Pure white	2000	1,5	10	40	11,500	2153963
2953 M25 RW	M25	Pure white	2000	1,6	13,6	30	16,000	2153966
2953 M32 RW	M32	Pure white	2000	1,6	17	20	21,500	2153969

PVC Polyvinylchloride

Dimensions



Authorised Channel Partner

