




Transient and lightning protection systems

Fine protection device TELE 4-F for ISDN RJ11

Data line protection device for analogue telecommunications systems

- In aluminium housing
- With 2-stage protection circuit
- Simple mounting
- Incl. 150 mm connection cable with RJ11 and/or RJ45 connectors
- Optimised bandwidth for TC systems
- DIN rail mounting with DLS-BS accessories (5082 38 2)

Application: For analogue telecommunication systems



Type	Version	Conne- tion system	Pack. pcs	Weight kg/100 pcs.	Item No.	Shopping list
RJ11-TELE 4-F	Fine protection, 4 wires	RJ11	1	14,000	5081977	

Connection options

RJ11-TELE 4-F	
Maximum continuous voltage AC	UC 120
Maximum continuous voltage DC	UC 170
Category	Type 2+3 / C2+C1
Lightning protection zone LPZ	1→3
Number of poles	4
Series resistance per wire	2,2 Ω ± 10 %
Total discharge current (8/20)	4
Total discharge current (10/350)	—
Protection level wire-wire	
Protection level wire-earth	
Protection level, wire-earth at 1 kV/μs (C3)	Up
Frequency range	0 - 18 MHz
Insertion loss	S21 ≤3
Temperature range	Θ -40-+80
Installation type	Connector/cable adapter
Connection system	RJ11
Protection rating	IP40
Earthing via:	Connection cable
Testing standard	IEC 61643-21

Authorized Channel Partner



Technical information

Invitations to tender	Declaration of conformity	Technical documents	3D product data	Certificates
RJ11-TELE 4-F / 5081977				