

starQuick clip



Can be arranged next to each other to size SQ-28.

Break load: with bolt DIN 96; diameter 4.5 mm, minimum break load at 20°.

starQuick clip Type SQ... a comprehensive programme of quality clips ideal for the use in outside areas such as parking garages, under bridges and on the exterior of steel structures. Climate conditions have no chance: the starQuick clips are made from UV weather-resistant polyamide.

The starQuick clips are available in 13 different sizes with a clamping range of 10–65 mm, allowing a problem-free installation on different pipe systems. starQuick is suitable for plastic and metal pipes, as well as electrical and sanitary installations. The clips can be installed on the wall and ceiling. Mounting is amazingly fast and uncomplicated, without the use of tools. Mounting of multiple pipes is also really easy:


- By arranging the single clips.
- By using the double bracket, allowing a firm hold and spacing by heavy loads.
- A rail system allows for an open spacing and numbering of the clips.

starQuick is reliable and can support heavy loads. A patented safety system guarantees that the pipes stay where they are. The pipe is secure in the all around closed clip.

Type	Clamping range D mm	Colour	Pack. pcs	Weight kg/100 pcs.	Item No.
SQ-10 LGR	9,5-12	Light grey	100	0,568	2146053
SQ-12 LGR	11,5-15	Light grey	100	0,540	2146061
SQ-15 LGR	14-16,5	Light grey	100	0,584	2146096
SQ-17 LGR	16-20	Light grey	100	0,640	2146118
SQ-20 LGR	19,5-23,5	Light grey	50	0,670	2146134
SQ-25 LGR	24-28	Light grey	50	0,970	2146207
SQ-28 LGR	27,5-32	Light grey	50	1,070	2146215
SQ-32 LGR	31,2-35,8	Light grey	50	1,230	2146258
SQ-36 LGR	35-40,1	Light grey	25	1,510	2146290
SQ-40 LGR	39,3-44,5	Light grey	25	1,710	2146320
SQ-47 LGR	44-50	Light grey	25	1,980	2146363
SQ-51 LGR	48-55	Light grey	15	2,250	2146444
SQ-59 LGR	58,5-65	Light grey	15	3,300	2146487

PA Polyamide

Dimensions



Type	Clamping range D mm	Dimension A mm	Dimension B mm	Dimension H mm	Breaking load kN
SQ-10 LGR	9,5-12	29	17	31,6	0,5
SQ-12 LGR	11,5-15	29	17	34,5	0,55
SQ-15 LGR	14-16,5	29	17	35,7	0,6
SQ-17 LGR	16-20	29	17	39,8	0,7
SQ-20 LGR	19,5-23,5	29	17	43,5	0,8
SQ-25 LGR	24-28	40	17	49,5	0,85
SQ-28 LGR	27,5-32	40	17	52,8	0,9
SQ-32 LGR	31,2-35,8	43	17	57,3	1
SQ-36 LGR	35-40,1	47	17	65,8	1,1
SQ-40 LGR	39,3-44,5	52	17	69,5	1,2
SQ-47 LGR	44-50	57	17	75,5	1,2
SQ-51 LGR	48-55	63	17	81	1,4
SQ-59 LGR	58,5-65	74	20	94,3	1,5

Authorised Channel Partner

