


Transient and lightning protection systems

Tapered pipe air-termination rod

- Suitable for wind loads according to Eurocode 1: DIN EN 1991-1-4
- From a free length of > 2.5 m, an additional fastening, e.g. insulated spacer is recommended
- Last metre is tapered from Ø 16 mm to Ø 10 mm, material: AlMgSi
- Matches stand system FangFix



Type	Length mm	Nominal size Ø mm	Pack. pcs	Weight kg/100 pcs.	Item No.	Shopping list
101 VL1500	1500	10/16	10	38,000	5401980	
101 VL2000	2000	10/16	10	55,000	5401983	
101 VL2500	2500	10/16	10	72,000	5401986	
101 VL3000	3000	10/16	10	88,000	5401989	
101 VL3500	3500	10/16	10	105,000	5401993	
101 VL4000	4000	10/16	10	120,000	5401995	

Alu Aluminium

Technical information

Invitations to tender	Declaration of conformity	Technical documents	3D product data	Certificates
101 VL1500 / 5401980				
101 VL2000 / 5401983				
101 VL2500 / 5401986				
101 VL3000 / 5401989				
101 VL3500 / 5401993				
101 VL4000 / 5401995				

Additional information

Catalogue



Transient and lightning

Brochure



Lightning and surge protection